



- 条码产品**
- 条码扫描器
    - 美国intermec
    - 美国Symbol
    - 意大利Datalogic
    - 台湾Gyoung
    - 美国HHP (honeywell)
    - 日本Opticon
    - 美国Microscan
    - 美国Metrologic
    - 台湾IMC
    - 美国PSC
    - 新大陆nls
    - 日本东研tohken
  - 条码打印机
    - 美国Intermec
    - 日本Toshiba-Tec
    - 美国斑马Zebra
    - 日本佐藤Sato
    - 日本Ring
    - 美国Datamax
    - 台湾Godex
    - 台湾TSC
    - 日本西铁城Citizen
    - 日本新盛shinsei
    - 德国CAB
    - 美国科立得Cognitive
  - 数据采集终端
    - 美国intermec
    - 美国Symbol
    - 日本Casio
    - 美国Metrologic
    - 台湾Gyoung
    - 日本keyence
    - 福建新大陆
    - 美国双成
    - 韩国蓝鸟bluebird
    - 韩国M3
  - 无线局域网
    - 美国intermec
    - 美国Symbol
  - 不干胶标签
  - 激光打印标签
  - 条码碳带
    - IMC系列碳带
    - 标准腊基碳带
    - 混合基碳带
    - 树脂基碳带
    - 水洗布专用树脂碳带
  - 条码打印软件
  - 条码检测仪
  - 条码打印机配件

美国Intermec条码扫描器 > Intermec SD61条码扫描器



**Intermec SD61 Wireless Base Station**

The SD61 allows you to more easily manage your Bluetooth scanners. This secure connection acts as a gateway to your host PC for up to 7 Intermec Bluetooth scanners. The SD61 houses the drivers to interact with the host PC, which means users need only scan the identifying bar code on the scanner to associate to the station and the host PC.

**Features**

- Easy set up - No need to install new software into your PC or host systems
- Lower acquisition costs - 1 base can connect up to 7 scanners
- Reliable wireless communication through Intermec advanced communication protocol
- Increased productivity and maneuverability by working up to 100m (328 ft) away from the base (open air)
- Investment protection with a wide choice of host connections
- Industrial grade - Intermec's rugged construction is ideal for warehouse & industrial applications
- Experience the flexibility to communicate with the Bluetooth? SD61 and SF51 Intermec Scanners

**Environment**

- Operating Temperature :-20° C/-4° F to 60° C/140° F
- Storage Temperature :-40° C/-40° F to 70° C/158° F
- Humidity :95% at 45° /113° F (non-condensing)
- Vibration and Shock protection :8G, from 10Hz to 500Hz, 2hr/axis, 3 axis
- Drop Survival :26 drops from 1.2m/3.9ft to concrete
- Sealing :IP53

**Physical Characteristics**

- Height :3.6cm (1.4 in.)
- Width :10.2cm (4 in.)
- Depth :11.5cm (4.5in.)
- Weight :150g (5.2oz)

**Power**

SD61 is powered via a host or universal 5 volt power supply; depending on the cable choice. 75mA at 5V +/- 10%



关闭

[条码业界新闻](#) | [网站地图](#) | [条码行业动态](#)

版权所有(C) 2002-2011 上海全亨科技

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail#intermeccorp.com

电话: 021-51088451 51088452 传真: 021-50935062

