

首 页 关于公司 条码产品 自主开发 应用方案 下载中心 条码知识 联系我们 服务支持 人才招聘

条码产品

- 条码扫描器
 - 美国intermec
 - 美国Symbol
 - 意大利Datalogic
 - 台湾Gyong
 - 美国HHP (honeywell)
 - 日本Opticon
 - 美国Microscan
 - 美国Metrologic
 - 台湾IMC
 - 美国PSC
 - 新大陆nls
 - 日本东研tohken
- 条码打印机
 - 美国Intermec
 - 日本Toshiba-Tec
 - 美国斑马Zebra
 - 日本佐藤Sato
 - 日本Ring
 - 美国Datamax
 - 台湾Godex
 - 台湾TSC
 - 日本西铁城Citizen
 - 日本新盛shinsei
 - 德国CAB
 - 美国科立得Cognitive
- 数据采集终端
 - 美国intermec
 - 美国Symbol
 - 日本Casio
 - 美国Metrologic
 - 台湾Gyong
 - 日本keyence
 - 福建新大陆
 - 美国双成
 - 韩国蓝鸟bluebird
 - 韩国M3
- 无线局域网
 - 美国intermec
 - 美国Symbol
- 不干胶标签
- 激光打印标签
- 条码碳带
 - IMC系列碳带
 - 标准腊基碳带
 - 混合基碳带
 - 树脂基碳带
 - 水洗布专用树脂碳带
- 条码打印软件
- 条码检测仪
- 条码打印机配件

美国Symbol条形码扫描器 > Symbol DS3478条形码扫描器

Symbol DS3478 手持激光二维无线远距离条码扫描器



Symbol DS3478条码枪简介

Dimensions: 7.34 in. L x 4.82 in. W x 2.93 in. D (18.65 cm H x 12.25 cm W x 7.43 cm D)

Weight (without cable): 14.6 oz. (414 gm)

Battery 2200 mAh Lithium Ion Battery

Battery charge time Fully charged (100%) in 3 hours

Color: Twilight Black/Yellow

Performance Characteristics

Light Source: 650 nm visible laser diode

Resolution 640 x 480

Minimum Element Width: 5 mil (0.127 mm)

Nominal Working Distance: See Decode Zone

Print Contrast: 25% minimum reflective difference

Roll (Tilt): +/- 50 degrees from normal

Pitch: +/- 60 degrees from normal

Skew (Yaw): +/- 180 degrees from normal

Codes UPC, EAN, UPC, EAN with Supplementals, UCC, EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39

Optic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants

Codes PDF417, microPDF417, Maxicode, Data Matrix (ECC 2000), Composite Codes, QR Code

Postal codes U.S. Postnet, U.S. Planet, U.K. Postal, Japan Postal, Australian Postal, Dutch Postal

Interfaces supported RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation, IBM 468X/469X, USB and Synapse

User Environment

Operating Temperature: 32? to 122?F (-0? to 50?C)

Storage Temperature: -40? to 140?F (-40? to 60?C)

Humidity: 5% to 95% relative humidity, noncondensing

Sealing: Sealed to IP65 specifications

Drop Specifications: Unit functions normally after repeated 6.5-ft. (2-m) drops to concrete

Ambient Light Immunity: Immune to direct exposure of normal office and factory lighting conditions, as well as direct exposure to sunlight:

Outdoor: 10,000 foot-candles/107,600 Lux

Electrostatic Discharge: Conforms to 15 kV air discharge and 8 kV of contact discharge

Radio specification

Radio range 100 meters direct line of sight.

Frequency 2.4 GHz

Regulatory

Input Transient Protection: IEC 1000-4-(2, 3, 4, 5, 6, 11)

EMI/RFI: FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Japan VCCI/MITI/ Dentori

Laser Safety: CDRH Class II, IEC Class 2



关闭

[条码业界新闻](#) | [网站地图](#) | [条码行业动态](#)

版权所有(C) 2002—2011 上海全亨科技

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail#intermeccorp.com

电话: 021-51088451 51088452 传真: 021-50935062

